



Environmental, Health, & Safety

## Hydride (SK) Gas Purifier Media

### CHEMICAL SAFETY DATA SHEET

#### SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

##### Product Details:

**Product:** Entegris Hydride (SK) Gas Purifier media  
**Product Number:** Entegris (SK) Series Hydride Gas purifiers and Gas Purification Systems  
**Chemical Name:** Inorganic  
**Product Use:** Hydride Gas purifier removes moisture and other molecular impurities from NH<sub>3</sub>, SiH<sub>4</sub>, GeH<sub>4</sub>, AsH<sub>3</sub>, PH<sub>3</sub>, B<sub>2</sub>H<sub>6</sub>, and Si<sub>2</sub>H<sub>6</sub> gas, and Hydride/Carrier gas mixtures.

**MSDS Number:** 8004351  
**Issue Date:** 6 November 2003  
**Rev. Date:** 6 May 2009  
**Revision:** D

##### Company Identification:

#### Entegris, Inc.

Entegris Malaysia Sdn. Bhd  
Lot 17, Phase 1, Kulim High-Tech Industrial Park  
Kulim, Kedah Durul Aman 09000  
Malaysia  
Information: (60) 4-4031266 (Malaysia)  
(858) 452-0124 (USA)

##### CHEMTREC Emergency telephone Numbers:

United States: 800-424-9300  
International: 703-527-3887 (collect)

#### SECTION 2 – COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components are a solid mixture contained inside the purifier stainless steel body.

<u>COMPONENT</u>	<u>CAS No.</u>	<u>PERCENT</u>
Manganese Dioxide	1313-13-9	60-80
Inorganic Oxide	Proprietary	20-40

Note: See Section 9 for Exposure Limits and Section 11 for Toxicological Information.

#### SECTION 3 – PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Black extrusions and Tan Beads  
**Odor:** Odorless  
**Specific Gravity (H<sub>2</sub>O=1):** 1.0 g/cc (Bulk Density)  
**Melting Point:** Not Determined  
**Vapor Pressure (mm Hg):** Not Applicable  
**Vapor Density (Air=1):** Not Applicable  
**Evaporation Rate:** Not Applicable  
**% Solubility in Water:** Insoluble  
**pH:** Not Determined

**SECTION 4 – HAZARDS IDENTIFICATION**

**\*\*Note\*\*** In the unlikely event that the purifier media is liberated from the purifier housing (whether intentional or accidental), health hazards may arise from the inhalation, ingestion, and/or contact with the skin or eyes.

**Appearance:** Black extrusions and tan beads. Odorless

**Health Hazards:** Causes eye, skin and respiratory tract irritation. May cause allergic skin and respiratory reaction. Harmful if swallowed. May cause gastrointestinal irritation, headache, nausea, vomiting and diarrhea.

Prolonged inhalation of manganese compounds above the ceiling exposure limit may cause lung irritation and central nervous system disorders. The symptoms simulate Parkinson's disease.

**Physical Hazards:** This product will remain stable when housed in the purifier body. Exposure of the product to air at room temperature may cause ignition.

When the Inorganic Oxide is first wetted, the product can heat up to the boiling point of water. Flood with water to cool down. Repeated and prolonged inhalation of crystalline silica in the form of quartz from occupational sources may cause cancer.

**Routes of Entry:**

Eyes: YES      Skin: YES      Inhalation: YES      Ingestion: YES

**Potential Health Effects:**

Eye Contact causes irritation or burns.

Skin Contact causes irritation and may cause sensitization or allergic reactions which may be accentuated by heat and humidity.

Inhalation causes upper respiratory irritation. Prolonged inhalation of manganese compounds above the ceiling exposure limit may cause lung irritation and central nervous system disorders. The symptoms simulate Parkinson's disease. Repeated and prolonged inhalation of crystalline silica in the form of quartz from occupational sources may cause cancer.

Ingestion is harmful. May cause nausea, abdominal discomfort, vomiting and diarrhea.

**Carcinogenicity: Inorganic Oxide**

Risk of cancer depends on route, duration and level of exposure.

NTP: YES      IARC: YES      US OSHA: YES

The International Agency for Research on Cancer (IARC) has classified crystalline silica as Group 2A, "probably carcinogenic to humans." The NTP and OSHA classify Quartz as a known carcinogen.

**Chronic Health Hazards:**

Refer to Potential Health Effects and Carcinogenicity.

**Medical Conditions Generally Aggravated by Exposure:**

May aggravate existing medical conditions such as allergies, dermatitis, asthma, bronchitis or any other respiratory ailment.

NOTE: See Section 9 for Exposure Limits, Section 11 for Toxicological Information and Section 12 for Ecological Information.

### SECTION 5 – FIRST AID MEASURES

In the unlikely event that the purifier media is liberated from the purifier body these health hazards may arise from inhalation, ingestion, and or/contact with the skin and/or eyes.

**Eye Contact:** Immediately flush eyes with plenty of water for at least 15 minutes, keeping eyelids open. Seek medical attention.

**Skin Contact:** Immediately wash skin with soap and plenty of water. If irritation persists, Seek medical attention.

**Inhalation:** Remove to fresh air. If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician.

**Ingestion:** Get medical attention!

**\*NOTE:** Inorganic Oxide is a desiccant and generates heat as it absorbs water. The used product can contain material of hazardous nature. Identify that material and symptomatically.

### SECTION 6 – FIRE-FIGHTING MEASURES

**Flash Point:** Not Determined  
**Auto-Ignition:** Not Applicable  
**LEL:** Not Applicable  
**UEL:** Not Applicable

<b>NFPA Hazard Classification: Manganese:</b>	Health: 0	Flammable: 2	Reactivity: 1
<b>HMIS Hazard Classification: Manganese:</b>	Health: 1*	Flammable: 2	Reactivity: 1

\* Indicates the possibility of chronic health effects. See Chronic Health Hazards in Section 3 for more information

**Extinguishing Media:** Use water, carbon dioxide or foam.

**Special Fire-Fighting Procedures:** Wear NIOSH-certified approved positive-pressure self-contained breathing apparatus and protective clothing as specified in country regulations (US OSHA 29 CFR 1910.156).

**Unusual Fire and Explosion Hazards:** This product will remain stable when housed in the purifier body. Exposure of the pyrophoric product to air at room temperature may cause ignition.

### SECTION 7 – ACCIDENTAL RELEASE MEASURES

Inorganic Oxide is a desiccant and generates heat as it absorbs water. **Allow media to cool before taking any action.**

Contain spillage and scoop up or vacuum. Avoid dusting. Refer to applicable country, state and local regulations for current response information.

It is recommended that each user establish an emergency response plan as specified in 29 CFR 1910.120. Such plan should include procedures applicable to proper storage, control and clean up of spills, including reuse or disposal as appropriate (see Section 13: Disposal Consideration).

**\*\*Note\*\*** In the unlikely event that the purifier media is liberated from the purifier body the above procedures should be followed. Additionally, proper exposure controls and personal protection equipment should be used (see Section 9: Exposure Control/Personal Protection), and disposal of the material should be in accordance with Section 13: Disposal Considerations.

### SECTION 8 - HANDLING AND STORAGE

**\*\*Note\*\*** In the unlikely event that the purifier media is liberated from the purifier body the following procedures should be observed.

Notify Safety personnel. **Allow media to cool before taking any action.** Wash thoroughly after handling media. Keep container closed. Avoid breathing dust. Keep away from sunlight, heat or fire. Store in cool, dry location away from incompatible materials.

### SECTION 9 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits Ingredients:	PEL-OSHA	TLV-ACGIH
Magnesium Dioxide CAS NO.: 1313-13-9	5 mg/m <sup>3</sup>	2 mg/m <sup>3</sup>
Inorganic Oxides CAS NO.: Proprietary	15 mg/m <sup>3</sup> (Total Dust) 5 mg/m <sup>3</sup> (Respirable)	10 mg/m <sup>3</sup> (Inhalable) 3 mg/m <sup>3</sup> (Respirable)

Unless otherwise noted, all values are reported as 8-hour Time-Weighted Averages (TWAs) and total dust (particulates only).

#### Malaysia Permissible Exposure Limits:

<u>Exposure Limits Ingredients:</u>	<u>8-Hour TWA Airborne Concentration mg/m<sup>3</sup></u>
Magnesium Dioxide CAS NO.: 1313-13-9	10 mg/m <sup>3</sup> (Inhalable particulate) 3 mg/m <sup>3</sup> (Respirable particulate)
Inorganic Oxides CAS NO.: Proprietary	0.05 mg/m <sup>3</sup> (Respirable fraction)

**Respiratory Protection:** A NIOSH-certified respirator recommended for dust if media is liberated from purifier body.

**Ventilation:** Use general ventilation; local exhaust ventilation as necessary to control any air contaminants to within their PELs or TLVs during exposure to media

**Protective Equipment:** Chemical goggles as needed to prevent irritation. Rubber or neoprene gloves. Body protection as necessary to prevent skin contact.

**SECTION 10 – STABILITY AND REACTIVITY**

**Stability:** Media is generally considered stable while housed inside purifier body.

**Avoid:** Heat and humidity.

**Incompatibility (Materials to Avoid):** Strong acids, easily oxidizable materials, chlorates and peroxides. When the Inorganic Oxide is first wetted, the product can heat up to the boiling point of water. Flood with water to cool down.

**Hazardous Decomposition or By-Products:** Toxic emissions may be released in a fire situation. Any material retained (such as hydrocarbons) by this product is reasonably expected to be released during decomposition.

**Polymerization:** Polymerization is not expected to occur.

**SECTION 11- TOXICOLOGICAL INFORMATION**

No data available.

**SECTION 12 – ECOLOGICAL INFORMATION**

**Ecotoxicity:** The biomagnifications of manganese in the food chain does not appear significant.

**Environmental Fate:** The transport of manganese in water is influenced by the solubility of the form present. Insoluble forms, such as manganese dioxide, are transported as sediment.

**SECTION 13 – DISPOSAL CONSIDERATIONS**

Country, state, and local disposal laws and regulations will determine the proper waste disposal/recycling/reclamation procedure. All waste materials should be reviewed to determine the applicable hazards (testing may be necessary). Disposal requirements are dependent on the hazard classification and will vary by location and the type of disposal selected.

**\*\*NOTE\*\*** Chemical additions, processing or otherwise altering this material may make the waste management information presented above incomplete, inaccurate or otherwise inappropriate.

As local regulations may vary; all waste must be disposed/recycled/reclaimed in accordance with country, state, and local environmental control regulations.

**SECTION 14 – TRANSPORT INFORMATION****INTERNATIONAL (IATA)**

<b>UN Number:</b>	1330
<b>Class/Division:</b>	4.1
<b>Proper Shipping Name:</b>	Magnesium Resinate
<b>Packing Group</b>	III

**MALAYSIA**

<b>UN Number:</b>	1330
<b>Class/Division:</b>	4.1
<b>Proper Shipping Name:</b>	Manganese Resinate
<b>Packing Group</b>	III

**UNITED STATES (DOT)**

**Identification Number:** UN1330  
**DOT Classification:** 4.1 Flammable Solid  
**DOT Proper Shipping Name:** Manganese Resinate  
**Packing Group:** III

**CANADA**

**PIN Number:** 1330  
**TDG Class:** 4.1 Flammable Solid  
**EC DGL:** Flammable Solid

**SECTION 15 – REGULATORY INFORMATION****US FEDERAL REGULATIONS**

**TSCA:** All materials are listed or compliant with the TSCA Inventory.

**SARA 311 and 312 Hazard Categories**

**Immediate (Acute) Health Hazard:** Yes  
**Delayed (Chronic) Health Hazard:** Yes  
**Fire Hazard:** Yes  
**Reactivity Hazard:** No  
**Sudden Release of Pressure:** No

**SARA Section 313 Notification:**

This product contains a toxic chemical (or chemicals) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

CHEMICAL NAME	CAS Number	%Wt.
Manganese Dioxide	1313-13-9	60-80

**OZONE DEPLETING SUBSTANCES (ODS):** This product neither contains nor is manufactured with an ozone depleting substance subject to the labeling requirements of the Clean Air Act Amendments 1990 and 40 CFR Part 82.

**VOLATILE ORGANIC COMPOUNDS (VOC):** None

**US STATE REGULATIONS**

**CALIFORNIA (Prop65):** The State of California has a regulation (Proposition 65) which identifies specific chemicals known to the State of California to cause cancer or birth defects. Proposition 65 requires a disclosure for products sold within the State of California containing an identified chemical. The following information is required by the State of California for this product:

**\*WARNING:** This product contains chemicals known to the State of California to cause cancer.

**Components:** Silica - crystalline, Quartz

(continued)

**CANADIAN REGULATIONS**

**DSL/NDSL:**

**WHMIS Classification:**

DSL

Class D Division 2 Subdivision A

Class D Division 2 Subdivision B

**EUROPEAN REGULATIONS**

**EINECS:** Yes

**OTHER REGULATIONS**

**MITI (Japan):** Yes

**AICS (AUSTRALIA):** Yes

**SECTION 16 – OTHER INFORMATION**

The chemical, physical and toxicological properties of this material have not been thoroughly investigated. Exercise due care.

Entegris is a registered trademark of Entegris Inc. or an affiliated company.

© 2009 Entegris Inc. or affiliated company. All rights reserved. The above information is believed to be current and accurate; however Entegris makes no warranty with respect to such information and assumes no liability for any loss or injury which may result from the use of this information. Users should conduct their own investigation to determine the suitability of the information.