

Integrated Flow Controller, NT6500

*For precision flow control
in legacy applications*

LIQUID FLOW CONTROLLER

Whether it's automation, process control or safety concerns that require accurate flow control of liquid chemicals and CMP slurry, the instrumentation must be clean, accurate and reliable. Using the latest electronic technology and high-purity materials, Entegris has designed a leading-edge liquid flow controller to allow for greater control of your process flow variables.

- PTFE wetted surfaces for high-purity applications
- Nonmetallic components for corrosion resistance
- Integral pressure transducer for additional process information
- One percent (1%) full scale accuracy for critical dispense applications
- Compact footprint for easy field installs with limited space
- Fast response for accurate dispense rates

CONSTRUCTED FOR COMPATIBILITY

The patented Integrated Flow Controller, NT6500 was developed for use in ultra high-purity liquid chemical instruments and slurry applications.

The instrument's valve seat and diaphragm are designed to minimize dead volume and fluid shear, reducing the possibility of process contamination. Featuring fluoropolymers for wetted parts and inert materials for nonwetted parts, the Integrated Flow Controller, NT6500 is resistant to harsh chemical environments and external spraydowns.



ADVANCED TECHNOLOGY

The Integrated Flow Controller, NT6500 utilizes dual PTFE valve diaphragms for fluid containment and contamination protection. Featuring the latest motorized valve and flowmeter technology, encapsulated internal electronics control all aspects of the flow controller. The unit is activated by a setpoint signal (i.e., 4-20 mA, 0-10 Vdc, 0-5 Vdc or via DeviceNet™ communication) to maintain fluid flow at the desired setpoint.

APPLICATIONS



Entegris is solving today's flow control challenges using the Integrated Flow Controller, NT6500. Combined with Entegris' differential pressure based flowmeter and leading-edge control valve technology, the closed-loop flow controller is ideal for:

- Continuous flow control for critical dispense applications
- CMP slurry dispense to replace existing peristaltic pumps
- Batch control for chemical spiking and blending
- On-demand chemical mixing applications

DEVICENET COMMUNICATION

With the optional DeviceNet communication protocol, critical diagnostics are available for alarms, troubleshooting and preventive maintenance. Local LED indicators provide network and flow controller status.

SPECIFICATIONS

Materials	Wetted parts	Body	PTFE
		Diaphragms	PTFE
		Sensor interface	PFA or CTFE
		Primary o-ring	Kalrez®
	Nonwetted parts	Polypropylene, FEP, PVDF and Viton® (In addition to materials listed above)	
Process temperature	10 – 65°C (50 – 149°F)		
Electrical input	24 Vdc (±10%) @ 1 amp 24 Vdc (±10%) @ 1.15 amp for DeviceNet		
Electrical output	Two 4–20 mA electrically isolated outputs, one for flow and one for pressure or DeviceNet communication		
Flow measurement	±1% of full scale from 20 – 100% of flow range ±2.5% of full scale from 10 – 20% of flow range (Calibrated using deionized water at 23°C [73°F])		
Repeatability	±0.5% of full scale from 20-100% of flow range ±1% of full scale from 10-20% of flow range		
Pressure measurement range	0 – 414 kPa (0 – 60 psig)		
Minimum operating pressure (at the inlet)	69 kPa (10 psig)		
Maximum operating pressure	414 kPa (60 psig)		
Over-pressure limit	690 kPa (100 psig)		
Pressure measurement accuracy	±1% of full scale (includes combined effects of linearity, hysteresis and repeatability)		
Electrical enclosure	IP54		
Reliability	Wetted parts, >3 million cycles		
Response time	<3 seconds from 10 to 95% of full scale flow range		
Setpoint input signal	4 – 20 mA, 0 – 10 Vdc, 0 – 5 Vdc or DeviceNet communication		
Approvals	 		

Note: Specifications are subject to change without notice. Please consult the factory for the most current information.

ORDERING INFORMATION

Integrated flow controller, NT 6500: part number

6500- - - - -U3

..... **Primary/secondary seal**

U3 = Kalrez 6375 UP/Viton

..... **Sensor interface**

P7 = CTFE (for acid, bases and oxidants, typically)

P8 = PFA (for solvents and temperatures >40°C [104°F], typically)*

..... **Setpoint input signal, controller type**

A = 4–20 mA, continuous

B = 0–10 Vdc, continuous

C = 0–5 Vdc, continuous

K = 4–20 mA, batch

L = 0–10 Vdc, batch

M = 0–5 Vdc, batch

D = DeviceNet communication

..... **Electrical connector type**

AM12 = PVC-jacketed 12' cable set, DeviceNet communication only

B06 = FEP-jacketed 6' pigtail electrical cable

B12 = FEP-jacketed 12' pigtail electrical cable

B30 = FEP-jacketed 30' pigtail electrical cable

D00 = Polypropylene connector (cable not included)

D06 = Polypropylene connector and 6' PVC cable

D12 = Polypropylene connector and 12' PVC cable

D30 = Polypropylene connector and 30' PVC cable

..... **Inlet/outlet port connection**

F02 = ¼" Flaretek tube fitting

F03 = ⅜" Flaretek tube fitting

F04 = ½" Flaretek tube fitting

F06 = ¾" Flaretek tube fitting

..... **Flow range****

T0 = 0–50 mL/min T5 = 0–2.5 L/min

T1 = 0–125 mL/min T6 = 0–5 L/min

T2 = 0–250 mL/min T7 = 0–10 L/min

T3 = 0–500 mL/min T8 = 0–20 L/min

T4 = 0–1250 mL/min T9 = 0–40 L/min

* Selection is dependent on application and chemical media. Please contact Entegris for best selection.

** Flow ranges are scaled to zero flow, measurement is from 10 to 100% of full scale flow range.

Product specified with a flared tube connection is packaged with two PVDF nuts. For alternative nut materials, or custom configurations and specifications, please contact the factory. (Note: Specifications are subject to change without notice. Please consult the factory for the most current information.)

FOR MORE INFORMATION

Please call your Regional Customer Service Center today to learn what Entegris can do for you. Visit entegris.com and select the Contact Us link to find the customer service center nearest you.

TERMS AND CONDITIONS OF SALE

All purchases are subject to Entegris' Terms and Conditions of Sale. To view and print this information, visit entegris.com and select the Terms & Conditions link in the footer.



Corporate Headquarters
129 Concord Road
Billerica, MA 01821
USA

Customer Service
Tel +1 952 556 4181
Fax +1 952 556 8022
Toll Free 800 394 4083

Entegris®, the Entegris Rings Design™, Pure Advantage™ and Flaretek® are trademarks of Entegris, Inc. Kalrez® and Viton® are registered trademarks of E. I. du Pont de Nemours and Company. DeviceNet™ is a trademark of the ODVA, Inc.

©2004–2016 Entegris, Inc. | All rights reserved. | Printed in the USA | 3963-1867ENT-1216