

# Trinzik™ UPW Ultrapure Water Filters

*Reduce defect-causing impurities  
using high-performance, ultrapure  
and DI water filtration*

Trinzik™ UPW filters are designed for high-performance filtration of bulk ultrapure and deionized (DI) water in facilities and point-of-tool applications. These reliable filters provide excellent retention of defect-causing contaminants, and are suited for water filtration in semiconductor, hard disk drive manufacturing, flat panel display (LCD, LED, OLED, AMOLED, plasma), and solar/photovoltaic industries.



## APPLICATIONS

- Make-up loops
- Polish loops
- Resin trap and general process tool water
- Low cost-of-ownership alternative to ultrafiltration (UF)
- Advanced UF guard filters

## FEATURES & BENEFITS


<b>High-porosity, hydrophilic PTFE membrane</b>	Enables high flow rate performance and reduces operational costs
<b>Small pore size membrane design</b>	Advanced particle removal increases yield
<b>Polypropylene (PP) construction</b>	Lower extractables ensure clean filtration operations

## SPECIFICATIONS

<b>Materials of construction</b>	Membrane	Hydrophilic PTFE
	Supports, core, sleeve	Polypropylene (PP)
	O-ring	E-FKM, silicone, EPDM, FKM
<b>Retention rating</b>	15 nm, 20 nm, 0.1 µm, 0.1 µm DI	
<b>Cartridge connections</b>	Code 0 (222 Flat), Code 5 (222-Fin), Code 6 (226 Flat), Code 7 (226 Fin)	
<b>Maximum operating conditions</b>	Maximum forward differential pressure:	
	5.5 bar (80 psid) @ 25°C (77°F)	
	1.7 bar (25 psid) @ 80°C (176°F)	
	Maximum reverse differential pressure:	
	3.4 bar (50 psid) @ 25°C (77°F)	
	Maximum temperature:	
	80°C (176°F)	
<b>Dimensions</b>	Length	10", 20", 30", 40"
	Diameter	69 mm (2.7")


## DIMENSIONS

Code 0 - 222 Flat



Length	A	B
10"	276.1 mm (10.9")	257.8 mm (10.2")
20"	522.5 mm (20.6")	504.2 mm (19.9")
30"	766.3 mm (30.2")	748 mm (29.5")
40"	1012.8 mm (39.9")	994.4 mm (39.2")


Code 5 - 222 Fin



Length	A	B
10"	315 mm (12.4")	298.5 mm (11.8")
20"	561.3 mm (22.1")	544.8 mm (21.5")
30"	805.2 mm (31.7")	788.7 mm (31.1")
40"	1051.6 mm (41.4")	1035 mm (40.8")


## DIMENSIONS (CONTINUED)

Code 6 - 226 Flat



Length	A	B
10"	276.9 mm (10.9")	265.4 mm (10.5")
20"	523.2 mm (20.6")	511.9 mm (20.2")
30"	767.1 mm (30.2")	755.7 mm (29.8")
40"	1013.5 mm (39.9")	1002 mm (39.5")


Code 7 - 226 Fin




Length	A	B
10"	316.5 mm (12.5")	306.1 mm (12.1")
20"	562.9 mm (22.2")	552.5 mm (21.8")
30"	806.7 mm (31.8")	796.3 mm (31.4")
40"	1053 mm (41.5")	1042.7 mm (41.1")

## PERFORMANCE DATA


Trinzik UPW 10" Cartridges




Trinzik UPW 30" Cartridges



Trinzik UPW 20" Cartridges




Trinzik UPW 40" Cartridges



## ORDERING INFORMATION

Trinzik UPW Ultrapure Water Filters: part number



## FOR MORE INFORMATION

Please call your Regional Customer Service Center today to learn what Entegris can do for you. Visit [entegris.com](http://entegris.com) and select the [Contact Us](#) link to find the customer service center nearest you.

## TERMS AND CONDITIONS OF SALE

All purchases are subject to Entegris' Terms and Conditions of Sale. To view and print this information, visit [entegris.com](http://entegris.com) and select the [Terms & Conditions](#) link in the footer.



### Corporate Headquarters

129 Concord Road  
Billerica, MA 01821  
USA

### Customer Service

Tel +1 952 556 4181  
Fax +1 952 556 8022  
Toll Free 800 394 4083

Entegris®, the Entegris Rings Design®, and other product names are trademarks of Entegris, Inc. as listed on [entegris.com/trademarks](http://entegris.com/trademarks). All third-party product names, logos, and company names are trademarks or registered trademarks of their respective owners. Use of them does not imply any affiliation, sponsorship, or endorsement by the trademark owner.

©2017-2020 Entegris, Inc. | All rights reserved. | Printed in the USA | 4448-8333ENT-1120